

Blackout



Performance Data

Total Solar Energy Reduction	84%
Solar Energy Reflected	36%
Solar Energy Absorbed	63%
Solar Energy Transmittance	1%
Visible Light Transmittance	0%
Visible Light Reflected	17%
Ultra Violet Light Reflected	99%
Shading Coefficient	0.19
Solar Heat Gain Coeff. (g Value)	
Emissivity	
Glare Reduction	100%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	5 Years

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️

Window Film Notes

Zero vision and virtually total opacity makes Blackout the ideal choice for absolute screening.