

# DC 22



## Performance Data

Total Solar Energy Reduction	70%
Solar Energy Reflected	37%
Solar Energy Absorbed	45%
Solar Energy Transmittance	18%
Visible Light Transmittance	22%
Visible Light Reflected	16%
Ultra Violet Light Reflected	99%
Shading Coefficient	.35
Solar Heat Gain Coeff. (g Value)	.30
Emissivity	.84
Glare Reduction	75%



## Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️    Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️  
N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️

## Window Film Notes

Very good solar heat and glare reduction with a low internal reflectance.