

Safety & Security - 4Mil Clear



Performance Data

Total Solar Energy Reduction	17%
Solar Energy Reflected	8%
Solar Energy Absorbed	15%
Solar Energy Transmittance	77%
Visible Light Transmittance	89%
Visible Light Reflected – Interior	9%
Visible Light Reflected – Exterior	9%
Ultra Violet Light Reflected	99%
Shading Coefficient	.95
Solar Heat Gain Coeff. (g Value)	.83
Emissivity	.90
Glare Reduction	1%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️

Window Film Notes

An optically clear film when viewed from both inside and out. An excellent film to upgrade glass to conform with Health & Safety, Regulation 14. ASTM D4830 puncture test 32kg. Gauge 100 microns.



Tel/Fax: 01428 751004
Email: sales@solarcontrol.co.uk
Web: www.solarcontrol.co.uk