

# Silver 20 (Dark)



## Performance Data

Total Solar Energy Reduction	76%
Solar Energy Reflected	50%
Solar Energy Absorbed	39%
Solar Energy Transmittance	11%
Visible Light Transmittance	16%
Visible Light Reflected	58%
Ultra Violet Light Reflected	99%
Shading Coefficient	.28
Solar Heat Gain Coeff. (g Value)	.24
Emissivity	.70
Glare Reduction	82%



## Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️    Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️  
N/A ☀️☀️☀️☀️☀️☀️☀️☀️

## Window Film Notes

This popular solar reflective sputtered film, offers excellent solar heat and glare rejection, giving the building a modern mirror appearance.



T: 01428 751004  
E: sales@solarcontrol.co.uk  
W: www.solarcontrol.co.uk