

Silver Shade



Performance Data

Total Solar Energy Reduction	70%
Solar Energy Reflected	40%
Solar Energy Absorbed	42%
Solar Energy Transmittance	18%
Visible Light Transmittance	22%
Visible Light Reflected	41%
Ultra Violet Light Reflected	99%
Shading Coefficient	.33
Glare Reduction	76%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️
N/A ☀️☀️☀️☀️☀️☀️☀️☀️

Window Film Notes

This film has been specially designed to be applied to the internal side of polycarbonate, GPR and plastic substrates. The film has a high performance metallised coating, offering a very low mirror appearance, which allows the natural light to enter the room.