

# SL 70 B



## Performance Data

Total Solar Energy Reduction	51%
Solar Energy Reflected	32%
Solar Energy Absorbed	36%
Solar Energy Transmittance	38%
Visible Light Transmittance	70%
Visible Light Reflected	11%
Ultra Violet Light Reflected	99%
Shading Coefficient	.59
Solar Heat Gain Coeff. (g Value)	.51
Emissivity	.68
Glare Reduction	19%



## Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️    Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️  
N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️

## Window Film Notes

This film is virtually invisible once installed. This film offers a clear view both inside and outside the window. A very good film for summer heat rejection, but still allowing the natural sunlight to enter the room.